


3/4" Drive 12 Point Socket

- Double hex (12 pt.) fastener end design
- Off-corner loading design reduces fastener rounding
- Large markings offer easy size identification
- Double line (SAE) & knurled line (MM) to easily identify standard and metric sockets
- Manufactured to industrial specifications assuring a thin wall design with precise nut end dimensions
- Heat treated for long lasting durability
- Bright, full polish chrome finish easily wipes clean and resists corrosion
- Chrome vanadium alloy steel (Cr-V) for exceptional strength and durability
- Meets or exceeds ASME B107.110



 These sockets accessories should never be used on power drivers, pneumatic impact wrenches and/or extenders.

Article Code	Size	Overall Length (mm) (Dimension C)	Drive End (mm) (Dimension A)	Wrench End (mm) (Dimension B)	
ST16602SC	19.0 mm	47.5	36.0	28.5	6
ST16603SC	21.0 mm	49.5	36.0	31.5	6
ST16604SC	22.0 mm	49.5	36.0	32.5	6
ST16605SC	23.0 mm	49.5	36.0	33.5	6
ST16606SC	24.0 mm	49.5	36.0	34.5	6
ST16607SC	25.0 mm	50.0	36.2	35.0	6
ST16608SC	26.0 mm	50.0	37.2	36.0	6
ST16609SC	27.0 mm	52.0	38.2	36.0	6
ST16610SC	28.0 mm	52.0	39.2	36.0	6
ST16611SC	29.0 mm	52.0	40.2	38.0	6
ST16612SC	30.0 mm	54.0	42.2	38.0	6
ST16613SC	32.0 mm	56.0	44.2	38.0	6
ST16614SC	33.0 mm	56.0	46.2	38.0	6
ST16615SC	34.0 mm	56.0	47.2	38.0	6
ST16616SC	35.0 mm	56.0	48.2	42.0	6
ST16617SC	36.0 mm	58.0	50.2	42.0	6
ST16618SC	38.0 mm	60.0	52.5	45.0	4
ST16619SC	41.0 mm	64.0	56.0	45.0	4
ST16620SC	46.0 mm	68.0	62.0	48.0	4
ST16622SC	50.0 mm	72.0	68.0	48.0	2
ST16623SC	55.0 mm	76.0	74.0	48.0	2
ST16624SC	60.0 mm	78.0	80.0	48.0	2

Continued on next page