

THREADED STEM FITTING

260 UBZ/UBY

Medium Duty Institutional Castor **SERIES**
35 - 150 KGS



Castor

260 (American specification)
Armor steel, double ballrace swivel path frame heat treatment
Metal Finish: Black lacquer

Wheel

UBZ Hardness 84± Shore A (PU Blue, non-marking)
Polyurethane, PP core double precision ball bearing (Without threadguards)
Temperature range: -20°C to +90°C

UBY Hardness 84± Shore A (PU Blue, non-marking)
Polyurethane, PP core single precision ball bearing (With threadguards)
Temperature range: -20°C to +90°C



Threaded	mm	mm	mm	mm	mm	mm	mm	mm	mm	mm	daN	kgs
261 UBZ 040 T12	M12	30	60	20	40	20	8	28	***			35
261 UBZ 050 T12	M12	30	73	22	50	25	8	28	***			50
261 UBZ 063 T12	M12	30	90	30	63	30	12	40	***			80
261 UBY 075 T12	M12	30	119	34	75	32	10.1	40	**			100
261 UBY 100 T12	M12	30	133	32.5	100	32	10.1	40	**			115
261 UBY 125 T12	M12	30	157	32.5	125	32	10.1	40	**			135
261 UBY 150 T12	M12	30	185	45	150	32	10.1	40	**			150

Threaded stem 5/8" - 11 UNC x 30mm also available (Suffix T06) Option: Other fitting available on request

263 UBY 075 T12	M12	30	119	34	75	32	10.1	40	**			100
263 UBY 100 T12	M12	30	133	32.5	100	32	10.1	40	**			115
263 UBY 125 T12	M12	30	157	32.5	125	32	10.1	40	**			135
263 UBY 150 T12	M12	30	185	45	150	32	10.1	40	**			150

Threaded stem 5/8" - 11 UNC x 30mm also available (Suffix T06) Option: Other fitting available on request

264 UBY 075 T12	M12	30	119	34	75	32	10.1	40	**			100
264 UBY 100 T12	M12	30	133	32.5	100	32	10.1	40	**			115
264 UBY 125 T12	M12	30	157	32.5	125	32	10.1	40	**			135
264 UBY 150 T12	M12	30	185	45	150	32	10.1	40	**			150

Threaded stem 5/8" - 11 UNC x 30mm also available (Suffix T06) Option: Other fitting available on request

266 UBZ 040 T12	M12	30	60	20	40	20	8	28	***			35
266 UBZ 050 T12	M12	30	73	22	50	25	8	28	***			50
266 UBZ 063 T12	M12	30	90	30	63	30	12	40	***			80
266 UBY 075 T12	M12	30	119	34	75	32	10.1	40	**			100
266 UBY 100 T12	M12	30	133	32.5	100	32	10.1	40	**			115
266 UBY 125 T12	M12	30	157	32.5	125	32	10.1	40	**			135
266 UBY 150 T12	M12	30	185	45	150	32	10.1	40	**			150

Threaded stem 5/8" - 11 UNC x 30mm also available (Suffix T06) Option: Other fitting available on request

	mm	mm	mm	mm	TG	mm	daN	kgs
UBZ 040	40	20	8	28	-	***		35
UBZ 050	50	25	8	28	-	***		50
UBZ 063	63	30	12	40	-	***		80
UBY 075	75	32	10.1	40	PP	**		100
UBY 100	100	32	10.1	40	PP	**		115
UBY 125	125	32	10.1	40	PP	**		135
UBY 150	150	32	10.1	40	PP	**		150