



## Chain Saw

Satisfy Professional's Needs

UC3050A, UC3550A, UC4050A, UC4550A  
UC3051A, UC3551A, UC4051A, UC4551A

# Longitudinal motor provides better maneuverability.

Nut-fix style sprocket cover



300mm (12") UC3050A,  
350mm (14") UC3550A,  
400mm (16") UC4050A,  
450mm (18") UC4550A



**Tool-less saw chain/  
tension adjustment**

300mm (12") UC3051A, 350mm (14") UC3551A,  
400mm (16") UC4051A, 450mm (18") UC4551A

# New adjustment lever for easier tool-less saw chain/ tension adjustment

## UC3051A, UC3551A, UC4051A, UC4551A

- extendable to allow for:
  - Easier saw chain tightening
  - Higher tightening torque
- can be quickly retracted at any angle.
- reduces the projections on Sprocket cover than ever.



Handles with Soft Grip

## UC3050A, UC3550A, UC4050A, UC4550A

Employ newly designed nut-fix style Sprocket cover to hold Saw chain and Guide bar with two nuts.



### Improved oil pump

keeps the delivery of chain oil constant regardless of temperature and the oil viscosity.



### Increased oil tank capacity

200 mL



### Large view window of Oil tank allows operator to easily check oil level.



### Large separate-type metal spike bumper

An optimum design has been achieved by employing separate-type. The spike grips workpiece firmly to provide more control.

Chain Saw	UC3051A 300mm (12") / UC3551A 350mm (14") / UC4051A 400mm (16") / UC4551A 450mm (18")				153
	UC3050A 300mm (12") / UC3550A 350mm (14") / UC4050A 400mm (16") / UC4550A 450mm (18")				153

	UC3051A / UC3551A / UC4051A / UC4551A	UC3050A / UC3550A / UC4050A / UC4550A
Double Insulation	1,800W	w1,800W
Brake	870m (2,900ft)	870m (2,900ft)
Torque Limiter	UC3051A : 300mm (12")	UC3050A : 300mm (12")
Soft Start	UC3551A : 350mm (14")	UC3550A : 350mm (14")
Automatic Oiling	UC4051A : 400mm (16")	UC4050A : 400mm (16")
Chain Brake	UC4551A : 450mm (18")	UC4550A : 450mm (18")
<b>Chain blade</b>	Pitch : 3/8" Gauge : 0.050"	Pitch : 3/8" Gauge : 0.050"
<b>Sound pressure level</b>	90.8dB(A)	90.8dB(A)
<b>Sound power level</b>	101.8dB(A)	101.8dB(A)
<b>Dimensions (L x W x H)</b>	505x200x220mm (19-7/8"x7-7/8"x8-5/8")	505x196x220mm (19-7/8"x7-3/4"x8-5/8")
<b>Net weight*</b>	UC3051A : 5.4kg (11.9lbs)	UC3050A : 5.4kg (11.9lbs)
	UC3551A : 5.5kg (12.1lbs)	UC3550A : 5.5kg (12.1lbs)
	UC4051A : 5.6kg (12.3lbs)	UC4050A : 5.6kg (12.2lbs)
	UC4551A : 5.7kg (12.5lbs)	UC4550A : 5.7kg (12.4lbs)
<b>Power supply cord</b>	0.3m (0.98ft)	0.3m (0.98ft)

Dimensions : excluding blade and guide bar

Standard Equipment : Chain Blade, Guide Bar, Guide Bar Cover, Hook Complete, Wrench (UC3050A / UC3550A / UC4050A / UC4550A)

\*weight according to EPTA-Procedure 01/2003 Items of standard equipment and specifications may vary by country or area.

# Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN BE-AB