

Stainless Strainer Screwed Type



Model	WSSS-10	
Applicable Fluid	Steam, Water, General liquid	
Applicable Pressure	Max. 0.98MPa/1.6MPa	
Applicable Temperature	Max. 180°C	
Connecting Method	JIS PT Screwed	
Hydraulic Testing	2.1 MPa at Water Pressure	
Material	BODY	SSC13
	TRIM	STS 304
Size	L	H
15A	60	61
20A	95	68
25A	83	60
32A	104	70
40A	108	82
50A	126	88

Stainless Ball Valve – 1PCS, 3PCS



WSB-1SP



WSB-3SP

Model	WSB-1SP	WSB-3SP
Applicable Fluid	Water, General liquid	
Applicable Pressure	Max. 0.98 MPa/1.6MPa	
Applicable Temperature	Max. 150°C	
Connecting Method	JIS PT Screwed	
Hydraulic Testing	2.5 MPa at Water Pressure	
Material	BODY	SSC 13
	BALL	STS304
	SEAT	PTFE

Size	WSB-1SP (One-Piece)		WSB-3SP (3-Piece)			
	Screwed		Screwed		Butt Weld	
	L	H	L	H	L	H
15A	56	67	65	106	72	104
20A	59	73	80	120	83	119
25A	70	85	85	128	95	129
32A	76	100	109	154	111	155
40A	82	112	118	165	120	166
50A	95	127	132	188	145	187

Stainless 3-Way Ball Valve (T type)



Model	WSB-3FL	
Applicable Fluid	Water, Steam, Oil	
Applicable Pressure	Max. 0.98MPa/1.6MPa	
Applicable Temperature	Max. 150°C	
Connecting Method	JIS 10K Flanged	
Hydraulic Testing	2.1 MPa at Water Pressure	
Material	BODY	SSC 13
	TRIM	TEFLON/SSC 13
Size	L	H
25A	180	70
32A	200	75
40A	220	90
50A	235	104
65A	260	153
80A	280	187
100A	320	206
125A	380	252
150A	440	244
200A	550	283
250A	670	345
300A	720	420

Stainless 4-Way Ball Valve



Model	WSB-4FL	
Applicable Fluid	Water, Steam, Oil	
Applicable Pressure	Max. 0.98 MPa/1.6MPa	
Applicable Temperature	Max. 150°C	
Connecting Method	JIS 10K Flanged	
Hydraulic Testing	2.5 MPa at Water Pressure	
Material	BODY	SSC 13
	TRIM	TEFLON/SSC 13
Size	L	H
15A	150	55
20A	160	55
25A	180	70
32A	200	75
40A	220	90
50A	240	104
65A	260	153
80A	280	187
100A	320	206
125A	380	252
150A	440	244
200A	550	283
250A	670	345
300A	720	420

■ Please contact us for other specifications.

Stainless Water hammer cushion (Spring Type)



Model	WHCS-10/WHCS-20		
Applicable Fluid	Water, General liquid		
Applicable Pressure	Max. 0.98 MPa / Max. 1.96 MPa		
Applicable Temperature	Max. 80 °C		
Connecting Method	JIS10K Flanged/JIS20K Flanged		
Hydraulic Testing	(1.5 MPa / 3.0MPa) at Water Pressure		
Material	BODY	STS304 / STS316	
	SPRING	STS 304	
	TRIM	STS 304	
Size	H	D	C
50A	132	155	120
65A	145	175	140
80A	170	185	150
100A	208	210	175
125A	230	250	210
150A	259	280	240
200A	302	330	290
250A	360	400	355
300A	500	445	400

■ Please contact us for other specifications.

Flange Adaptor



Model	WGFA-10	WGFA-20
Applicable Fluid	Water, Steam, Oil, Gas	
Applicable Pressure	Max. 0.98MPa	Max. 1.96MPa
Connecting Method	Flange-Grooved End	
Hydraulic Testing	(1.5 MPa / 3.0 MPa) at Water Pressure	
Material	Pipe	SPP / STS304
	Flange	SF390A / SSC13
Size	O.D	H
50A	60.5	80
65A	76.3	85
80A	89.1	85
100A	114.3	90
125A	139.8	95
150A	165.2	100
200A	216.3	115
250A	267.4	120
300A	318.5	120