

Stainless Swing check Valve – Screwed Type



Model	WSCS-1	
Applicable Fluid	Water, Steam, Oil	
Applicable Pressure	Max. 0.98 MPa / 1.6 MPa	
Applicable Temperature	Max. 180 °C	
Connecting Method	JIS PT Screwed	
Hydraulic Testing	2.5 MPa at Water Pressure	
Material	BODY	SSC13
	TRIM	STS 304
Size	L	H
15A	62	69
20A	73	75
25A	83	85
32A	99	104
40A	115	118
50A	134	137

Stainless Hammerless check Valve



Model	WSHL-1	
Applicable Fluid	Water, General liquid	
Applicable Pressure	Max. 0.98 MPa / 1.6 MPa	
Applicable Temperature	Max. 120 °C	
Connecting Method	JIS 10K Flanged	
Hydraulic Testing	2.5 MPa at Water Pressure	
Material	BODY	SSC13
	TRIM	STS304 / TEFLON
Size	L	H
40A	160	120
50A	180	135
65A	200	145
80A	210	150
100A	217	160
125A	255	190
150A	280	200
200A	415	235

- Use Dual Check Valves or Pan Check Valves for Horizontal Pipes.
- Made to order for sizes max. 250A
- Made to order for operating pressure 20K products

Stainless Pan check Valve



WPSC-10



WPSC-10S

Model	WPSC-10 / WPSC-10S			
Applicable Fluid	Water, General liquid			
Applicable Pressure	Max. 0.98 MPa / 1.6 MPa			
Applicable Temperature	Max. 180 °C			
Connecting Method	JIS 10K WAFER / JISPT Screwed			
Hydraulic Testing	2.5 MPa at Water Pressure			
Material	BODY	SSC13		
	TRIM	STS 304		
Size	A Type		B Type	
	L	D	L	D
15A	16	40	16	40
20A	19	50	19	50
25A	22	60	28	68
32A	29	72	30	79
40A	32	86	36	86
50A	40	101	40	101
65A	46	117	49	121
80A	50	132	57	131
100A	60	150	68	156
125A	90	164	78	185
150A	105	196	94	207
200A	140	270	110	265

Stainless Foot Valve



Model	WSFT-1	
Applicable Fluid	Water, General liquid	
Applicable Pressure	Max. 0.98 MPa / 1.6 MPa	
Applicable Temperature	Max. 120 °C	
Connecting Method	JIS 10K Flanged	
Hydraulic Testing	2.5 MPa at Water Pressure	
Material	BODY	SSC13
	TRIM	SSC13
Size	D	H
40A	140	170
50A	155	190
65A	175	223
80A	185	260
100A	210	276
125A	250	333
150A	280	363
200A	330	420
250A	400	502
300A	445	450

- You must install vertically
- Made to order for sizes max. 350A
- Made to order for operating pressure 20K products

Stainless Strainer



Model	WHL-10	
Applicable Fluid	Steam, Water, General liquid	
Applicable Pressure	Max. 0.98 MPa / 1.6 MPa	
Applicable Temperature	Max. 180 °C	
Connecting Method	JIS 10K Flanged	
Hydraulic Testing	2.5 MPa at Water Pressure	
Material	BODY	SSC13
	TRIM	STS 304
Size	L	H
15A	120	60
20A	125	60
25A	155	75
32A	170	75
40A	180	91
50A	190	125
65A	215	133
80A	305	198
100A	365	240

Stainless Strainer



Model	WSCP-1L			
Applicable Fluid	Water, Steam, Oil			
Applicable Pressure	Max. 0.98 MPa / 1.6 MPa			
Applicable Temperature	Max. 180 °C			
Connecting Method	JIS 10K Flanged			
Hydraulic Testing	2.5 MPa at Water Pressure			
Material	BODY	SSC13		
	TRIM	SSC13 / STS304		
Size	A Type		B Type	
	L	H	L	H
65A	285	162	255	142
80A	305	204	280	170
100A	380	243	315	203
125A	394	295	345	213
150A	444	343	380	218
200A	540	415	484	247
250A	670	512	560	300
300A	765	585	720	350

- Made to order for sizes max. 350A
- Made to order for operating pressure 20K products