

Cast steel Ball Valve



WBB-1FL



WBB-1FG

Model	WBB-1FG / WBB-1FL	
Type	Gear / Lever	
Applicable Fluid	Gas	
Applicable Pressure	Max. 0.98MPa / 1.6Mpa	
Applicable Temperature	Max. 150°C	
Connecting Method	JIS 10K Flanged	
Hydraulic Testing	2.94 MPa at Water Pressure	
Material	BODY	SCPH2
	TRIM	TEFLON / STS304

Size	L		H
	40A	165	115
WBB-1FL	50A	178	120
	65A	190	153
	80A	203	162
	100A	229	191
	125A	356	211
WBB-1FG	150A	394	290
	200A	457	340
	250A	533	500
	300A	610	520

Stainless Butterfly Valve



WSBG-1



WSBL-1

Model	WSBL-1	WSBG-1
Applicable Fluid	water, Air, oil & Gas	
Applicable Pressure	Max. 1.6Mpa	
Applicable Temperature	5°C ~ 150°C	
Operating Type	LEVER ACTING	GEAR ACTING
Hydraulic Testing	2.5MPa at Water Pressure	
Seat Leak Test	1.6MPa at Water Pressure	
Connecting Method	JIS 10K WAFER	
Material	BODY	SSC13
	TRIM	PTFE / SSC13

Size	WSBL-1		WSBG-1	
	L	H	L	H
40A	43	168	43	185
50A	43	168	43	185
65A	46	172	46	200
80A	46	177	46	230
100A	52	188	52	262
125A	56	213	56	296
150A	56	222	56	336
200A	60	255	60	362
250A	—	—	68	432
300A	—	—	78	532

■ This product is for pure water. There is no guarantee in quality for use with pollutants, corrosive fluid or sea water.
 ■ The gear box material is GC200

Stainless Ball Valve Flanged type



WSB-1FL



WSB-1FG

Model	WSB-1FL	WSB-1FG
Type	Lever	Gear
Applicable Fluid	a chemical agent, Industrial water, Drinking water	
Applicable Pressure	Max. 0.98MPa / 1.6Mpa	
Applicable Temperature	Max. 180 °C	
Connecting Method	JIS 10K Flanged	
Hydraulic Testing	2.94 MPa at Water Pressure	
Material	BODY	SSC 13
	TRIM	TEFLON/STS 304

WSB-1FL		
Size	L	H
15A	108	82
20A	117	85
25A	127	95
32A	140	100
40A	165	115
50A	178	120
65A	190	153
80A	203	162
100A	229	191
125A	356	211
150A	395	290

WSB-1FG		
Size	L	H
200A	457	340
250A	533	500
300A	610	520

Stainless Ball Valve (Screwed type)



Model		WSB-20S	
Applicable Fluid		Industrial water, Drinking water	
Applicable Pressure		Max. 1.96MPa	
Applicable Temperature		5°C ~ 180°C	
Connecting Method		JIS PT Screwed	
Hydraulic Testing		2.94 MPa at Water Pressure	
Material	BODY	SSC13	
	TRIM	STS 304/TEFLON	

Size	WSB-20S	
	L	H
15A	48.5	46
20A	57	49
25A	68	57
32A	79	66
40A	88.5	74
50A	100.5	80

Stainless Gate Valve



Model	WSGN-1	
Applicable Fluid	Water, Steam, Oil	
Applicable Pressure	Max. 0.98MPa/1.6Mpa	
Applicable Temperature	Max. 180℃	
Connecting Method	JIS 10K Flanged	
Hydraulic Testing	2.5 MPa at Water Pressure	
Material	BODY	SSC13
	TRIM	SSC13 / STS304

Size	L	H
15A	80	100
20A	90	125
25A	100	142
32A	110	149
40A	125	164
50A	140	183
65A	170	247
80A	193	270
100A	210	337

Stainless Gate Valve



Model	WSGO-1	
Applicable Fluid	Water, Steam, Oil	
Applicable Pressure	Max. 0.98 MPa / 1.6Mpa	
Applicable Temperature	Max. 180 ℃	
Connecting Method	JIS 10K Flanged	
Hydraulic Testing	2.5 MPa at Water Pressure	
Material	BODY	SSC13
	TRIM	SSC13 / STS304

Size	L	H
50A	178	359
65A	190	410
80A	203	421
100A	229	546
125A	254	670
150A	267	772
200A	292	998
250A	342	1185
300A	356	1366

■ Made to order for sizes max. 350A
 ■ Made to order for operating pressure 20K products