

Stainless Gate Valve



Model	WSGS-1	
Applicable Fluid	Water, Steam, Oil	
Applicable Pressure	Max. 0.98 MPa / 1.6 MPa	
Applicable Temperature	Max. 180 °C	
Connecting Method	JIS PT Screwed	
Hydraulic Testing	2.5 MPa at Water Pressure	
Material	BODY	SSC13
	TRIM	SSC13 / STS304
Size	L	H
15A	56	95
20A	61	100
25A	65	115
32A	71	135
40A	79	155
50A	90	180

Stainless Globe Valve



Model	WSLN-1	
Applicable Fluid	Water, Steam, Oil	
Applicable Pressure	Max. 0.98 MPa / 1.6 MPa	
Applicable Temperature	Max. 180 °C	
Connecting Method	JIS 10K Flanged	
Hydraulic Testing	2.5 MPa at Water Pressure	
Material	BODY	SSC13
	TRIM	SSC13 / STS 304
Size	L	H
50A	194	185
65A	216	220
80A	241	243
100A	292	308

Stainless Globe Valve



Model	WSLO-1	
Applicable Fluid	Water, Steam, Oil	
Applicable Pressure	Max. 0.98 MPa / 1.6 MPa	
Applicable Temperature	Max. 180 °C	
Connecting Method	JIS 10K Flanged	
Hydraulic Testing	2.5 MPa at Water Pressure	
Material	BODY	SSC13
	TRIM	SSC13 / STS 304
Size	L	H
50A	203	296
65A	216	321
80A	241	367
100A	292	427
125A	356	498
150A	406	592
200A	495	665
250A	622	771
300A	698	901

- Made to order for sizes max. 350A
- Made to order for operating pressure 20K products

Stainless Globe Valve



Model	WSLS-1	
Applicable Fluid	Water, Steam, Oil	
Applicable Pressure	Max. 0.98 MPa / 1.6 MPa	
Applicable Temperature	Max. 180 °C	
Connecting Method	JIS PT Screwed	
Hydraulic Testing	2.5 MPa at Water Pressure	
Material	BODY	SSC13
	TRIM	SSC13 / STS304
Size	L	H
15A	68	95
20A	79	99
25A	89	99
32A	103	125
40A	118	130
50A	138	153

Stainless Swing check Valve



Model	WSCP-1S	
Applicable Fluid	Water, Steam, Oil	
Applicable Pressure	Max. 0.98 MPa / 1.6 MPa	
Applicable Temperature	Max. 180 °C	
Connecting Method	JIS 10K Flanged	
Hydraulic Testing	2.5 MPa at Water Pressure	
Material	BODY	SSC13
	TRIM	SSC13 / STS304
Size	L	H
15A	108	54
20A	117	59
25A	127	65
32A	140	75
40A	165	83
50A	203	96
65A	216	110
80A	241	125
100A	292	145

Stainless Swing check Valve



Model	WSCP-1L			
Applicable Fluid	Water, Steam, Oil			
Applicable Pressure	Max. 0.98 MPa / 1.6 MPa			
Applicable Temperature	Max. 180 °C			
Connecting Method	JIS 10K Flanged			
Hydraulic Testing	2.5 MPa at Water Pressure			
Material	BODY		SSC13	
	TRIM		SSC13 / STS304	
Size	A Type		B Type	
	L	H	L	H
65A	285	162	255	142
80A	305	204	280	170
100A	380	243	315	203
125A	394	295	345	213
150A	444	343	380	218
200A	540	415	484	247
250A	670	512	560	300
300A	765	585	720	350

- Made to order for sizes max. 350A
- Made to order for operating pressure 20K products